



LED High Bay Light U Series




Features

- CREE/Bridgelux LED chip.
- MeanWell driver.
- High power factor >0.9, low THD driver.
- Fin type heat sinker with cooper cylinder structure remarkably enhances the stability and lifespan.
- The anodic oxidation spinning reflector can be separated from the main body part, easy to transport.
- High light transmittance PC cover used upon the LED.
- Shell of 45°, 90°, 120° beam angle for optional.

Applications

Widely used in lighting of mines, workshops, factories, toll stations, gas stations, superstores, exhibition halls, gymnasiums, warehouses, etc..



Item No.	Size (ΦAxB)	Power	Voltage	Color	Beam Angle	Luminous Flux	CRI	Lifespan
V-MGC206U	160x100mm 6.3"x3.94"	60W	AC100-277V	2700K-6500K	45°/90°/120°	4,500lm	≥70	50,000
V-MGC209U	160x150mm 6.3"x5.91"	90W	AC100-277V	2700K-6500K	45°/90°/120°	7,300lm	≥70	50,000
V-MGC211U	160x180mm 6.3"x7.09"	110W	AC100-277V	2700K-6500K	45°/90°/120°	9,700lm	≥70	50,000
V-MGC213U	200x140mm 7.87"x5.51"	130W	AC100-277V	2700K-6500K	45°/90°/120°	10,800lm	≥70	50,000
V-MGC217U	220x220mm 8.66"x8.66"	170W	AC100-277V	2700K-6500K	45°/90°/120°	14,000lm	≥70	50,000
V-MGC220U	220x220mm 8.66"x8.66"	200W	AC100-277V	2700K-6500K	45°/90°/120°	17,000lm	≥70	50,000